

Date:	Project Name:
Type:	Part Number:



# FLARE SERIES

## LED SLIM CANOPY





### DESCRIPTION

The Flare series Square canopy is DLC Premium listed and ETL for wet locations with a rating of IP65. It's quick to install and aesthetically pleasing construction, with die-cast aluminum housing and shatter-resistant polycarbonate prismatic lens makes this fixture perfect for most outdoor lighting needs. Dustproof, sealed structure, 1/2" threaded conduit entrances on each side provide versatility and unmatched quality. This fixture comes with an option for microwave occupancy or photocell sensor, installed with a DC adapter. The canopy supports both pendant mounting and direct surface mounting ceiling and wall. The Slim Canopy fixture can be Pendant Mounted and accepts a 3/4" NPT Thread and can be mounted to multiple types of J-boxes. Ideal applications for parking garage, canopy, walkway and entrance lighting etc.

### FEATURES

- DLC Premium
- Aluminum Alloy & PC Material
- High and stable lumen output
- Energy-efficient
- Easy Installation & Maintenance
- Multi CCT & Wattage
- Dual Voltage 120-347V
- 7 year warranty

### APPLICATIONS

-  Parking structures
-  Storage areas
-  Shopping/Grocery centres
-  Entryways



Date:	Project Name:
Type:	Part Number:

## SPECIFICATION

ORDER#	MODEL#	WATTS	VOLTAGE (V)	CCT (K)	LUMENS	BEAM ANGLE	EFFICACY	CRI
R52017	RENO-SCP-40W-MW-DV-MCCT-R1	25W	120-347V	30/40/50K	3250 lm	140°	130 lm/W	>70
		30W			3900 lm			
		35W			4550 lm			
		40W			5200 lm			
R52018	RENO-SCP-75W-MW-DV-MCCT-R2	45W	120-347V	30/40/50K	5850 lm	140°	130 lm/W	>70
		55W			7150 lm			
		65W			8450 lm			
		75W			9750 lm			

## RENO SMART NLC SYSTEM ACCESSORIES

ORDER#	MODEL#	DESCRIPTION
R75001	RENO-RS-JK-BPDN-12V	Bluetooth 3.5mm Jack PIR Sensor for RENO Smart NLC System
R75002	RENO-RS-JK-BMWM-12V	Bluetooth 3.5mm Jack Microwave Sensor for RENO Smart NLC System
R75201	RENO-RS-GW-BCNW	Ceiling Mounted Gateway for RENO Smart NLC System
R75302	RENO-RS-RC-BNNG	7-Key Smart Wall Switch for RENO Smart NLC System
R75301	RENO-RS-RC-BNNN	5-Key Reset Remote



RENO-RS-JK-BPDN-12V



RENO-RS-JK-BMWM-12V



RENO-RS-GW-BCNW



RENO-RS-RC-BNNG



RENO-RS-RC-BNNN

Date:	Project Name:
Type:	Part Number:

## STANDALONE SENSORS

ORDER#	MODEL#	DESCRIPTION
R72001	RENO-SENSOR-PC-S	Photocell Sensor
R71002	RENO-SENSOR-MW-H	Dimming Microwave Sensor



RENO-SENSOR-PC-S



RENO-SENSOR-MW-H

## STANDALONE SENSOR REMOTE

ORDER#	MODEL#	DESCRIPTION
R73002	RENO-REMOTE-H	Remote Control



RENO-REMOTE-H

Date:	Project Name:
Type:	Part Number:

## DIMENSIONS




260mm  
(10.24")




88mm  
(3.46")

## MOUNTING OPTIONS

Rigid Conduit



Couduit Mount



Surface Mount

