

Date:	Project Name:
Type:	Part Number:



T8 TYPE A



FEATURES

- Direct plug-in & Safe Installation
- No UV or IR radiation
- High luminous efficiency
- Compatible with instant & programmed start ballast
- Operating temperature: -4°F to +113°F (-20°C to +45°C)
- CRI >83
- Rated Lifetime L70(hrs): >50,000
- 5 year warranty

APPLICATIONS

- Office Lighting
- Commercial Applications
- Retail Lighting
- Residential



Date:	Project Name:
Type:	Part Number:

SPECIFICATION

ORDER#	MODEL#	WATTS	SIZE	VOLTAGE (V)	LUMENS	BASE TYPE	BEAM ANGLE	CCT (K)
R41024	WLL-LEDT8BC9/840/HE	9W	4FT	BF	1800 lm	G13	320°	4000K
R41025	WLL-LEDT8BC9/850/HE	9W	4FT	BF	1800 lm	G13	320°	5000K
R41026	WLL-LEDT8BC10/830/HE	10W	4FT	BF	1700 lm	G13	320°	3000K
R41020	WLL-LEDT8BC13/840/HE	13W	4FT	BF	2200 lm	G13	320°	4000K
R41021	WLL-LEDT8BC13/850/HE	13W	4FT	BF	2200 lm	G13	320°	5000K

DIMENSIONS

