

Date		Project	
Type		Part Number	



ALL-IN-ONE PERFORMANCE LIGHTING

TYPE A T5

Type A T5 Tubes

Make the switch to T5 Type A LED lamps for an effortless upgrade from fluorescent tubes to modern, energy-saving LED technology. Designed for plug-and-play compatibility with existing electronic ballasts, this LED tube offers instant brightness, reduced energy consumption, and a long lifespan of up to 50,000 hours. Perfect for offices, schools, hospitals, retail spaces, and warehouses, it provides uniform, flicker-free lighting with excellent color clarity.



PRODUCT FEATURES

- NSF Listed: NSF/ANSI Standard 2 - Food Equipment
- Direct plug-in & Safe Installation
- No UV or IR radiation
- High luminous efficiency
- Compatible with instant & programmed start ballast
- High luminous efficiency
- Operating temperature: -4°F to +113°F (-20°C to +45°C)
- Rated Lifetime L70(hrs): >50,000
- 5 year warranty

KEY SPECIFICATIONS

Lamp Base	G5
Size	4.0 ft
Wattage	25.5W
Voltage	BF
CCT	3500K, 4000K, 5000K
Lumens	Up to 3600 lm
CRI	>83
Beam Angle	330°
Lifespan	50,000 hrs
Dimming	No




SPECIFICATIONS

Order#	Model	Size	Wattage	Voltage	CCT	Lumens	CRI	Beam Angle
R42021	RENO-LEDT5BC-25.5W-MCCT-48G	4.0 ft	25.5W	BF	35/40/5000K	3500/3600/3600 lm	>83	330°

DLC CERTIFICATION

Order#	Model	Application	DLC Standard	DLC Premium
R42021	RENO-LEDT5BC-25.5W-MCCT-48G	Replacement Lamps	S-59GT90	–

ACCESSORIES – MOUNTING




289/SN-15-PBT

Low profile rotary lock
T5 socket

Order#	Model	Description
-	289/SN-15-PBT	Low profile rotary lock T5 socket

DIMENSIONS

4 FT



Full Body Width: 45.2" (1148.1 mm)

Lens Width: 42" (1066.8 mm)

Thickness: 0.7" (17.8 mm)

Weight: n/a