

| | | | |
|------|--|-------------|--|
| Date | | Project | |
| Type | | Part Number | |



ALL-IN-ONE PERFORMANCE LIGHTING

BRILLIANCE Series

Fire Rated Slim Downlight

The Brilliance Series Fire Rated Recessed Downlights are designed to provide exceptional illumination. These downlights provide two hours of protection in the event of a fire and are perfect solution for installations with low ceiling clearance. High-quality mounting spring, quick connectors, and included junction box. The premium aluminum body of this LED downlight ensures superior durability and aesthetics compared to plastic options.



2 HOUR FIRE RATING
Tested to comply with UL 253,
ASTM E119 & CAN ULC 8101



PRODUCT FEATURES

- JA8 compliant
- Energystar Certified
- FT4-Rated Cable
- 2-Hour fire rating providing a reinforced and heat resistant steel casing
- IC-rated and Air-Tight ready and may be in direct contact with insulation
- Compatible with Soffit installations and can be installed in shallow plenum spaces
- Flicker-free 120V forward-phase triac dimming down to 5%
- 277-347V Driver Available
- Operating temperature: -4°F to +104°F (-20°C to +40°C)
- Rated Lifespan: L70 ~50,000 hrs
- 5 year warranty

KEY SPECIFICATIONS

| | |
|---------------------|--|
| Voltage | 120V |
| Sizes | 4" & 6" |
| Wattage | 9W, 15W |
| Lumens | 800 lm, 1100 lm |
| CCT | 27/30/35/40/5000K |
| Power Factor | >0.9 |
| CRI | >90 |
| Beam Angle | 108° |
| Dimming | 120V forward-phase TRIAC Dimming |
| Mounting | Recessed |
| Applications | Commercial, Residential, Retail Facilities |



EMERGENCY
BACKUP READY


SPECIFICATIONS - 4" FIRE RATED SLIM DOWNLIGHT

| Order# | Model | Wattage | Voltage | Lumens | Efficacy | CCT | Finish |
|--------|----------------------------|---------|---------|--------|----------|-------------------------------|--------|
| R36033 | RENO-LED-4-S12W-5CCT-WH-FR | 12W | 120V | 800 lm | 67 lm/W | 2700/3000 3500/ 4000/5000K | White |


SPECIFICATIONS - 6" FIRE RATED SLIM DOWNLIGHT

| Order# | Model | Wattage | Voltage | Lumens | Efficacy | CCT | Finish |
|--------|----------------------------|---------|---------|---------|----------|-------------------------------|--------|
| R36032 | RENO-LED-6-S15W-5CCT-WH-FR | 15W | 120V | 1100 lm | 73 lm/W | 2700/3000 3500/ 4000/5000K | White |

ACCESSORIES – MOUNTING



R39108
RENO-MP4
4" Mounting Plate without clip



R39109
RENO-MP6
6" Mounting Plate without clip



R39105
RENO-HBL015-347V-D
AC277-347V driver for 4" & 6"
slim potlight

| Order# | Model | Description |
|--------|--------------------|---|
| R39108 | RENO-MP4 | 4" Mounting Plate without clip (Opening 108mm) |
| R39109 | RENO-MP6 | 6" Mounting Plate without clip (Opening 158mm) |
| R39105 | RENO-HBL012-347V-D | AC277-347V driver for 4" & 6" slim potlight, Non-dimmable |

ACCESSORIES – EMERGENCY LED DRIVERS




R83000
RENO-EM-H08
Emergency LED Driver
(100-347V AC, 50-60Hz, 12W)

| Order# | Model | Description |
|--------|-------------|--|
| R83000 | RENO-EM-H08 | Emergency LED Driver (100-347V AC, 50-60Hz, 12W) |


DIMENSIONS

4"



*NOTE: Width in ceiling needed for the driver to fit is 3" Cut hole size 4-1/4" (108mm)

6"



*NOTE: Width in ceiling needed for the driver to fit is 3" Cut hole size 6.26" (159mm)