


Date: _____ Project: _____

Type: _____ Part #: _____

Aim Series

High Power Back-Lit Panel w/ Sensor Compatibility

RENO Lighting's AIM Series high-power sensor-ready backlit panel is a versatile lighting solution for modern commercial environments.
Featuring an integrated sensor-ready port compatible with PIR and Bluetooth controls, it delivers flexible functionality in a seamless design. Engineered for visual comfort, the AIM Series offers less than 5% flicker, 90 CRI, uniform illumination, and long maintenance-free performance for a wide range of applications.

Product Features

- Available sizes: 1x4, 2x2, 2x4
- Integrated 2.5 mm sensor port. Compatible with both standalone and smart sensors
- Formed SPCC cold-rolled steel with powder-coated white finish
- PMMA lens
- Backlit technology offers even light distribution without shadowing
- Less that 5% flicker to minimize eye strain and visual fatigue
- Damp location rated
- Operating temp: -4°F to 104°F (-20°C to 50°C)
- Rated Lifetime > 100,000 hours
- 10 Year Limited Warranty

Specifications

Voltage	120-347V AC
Selectable Wattages	1x4: 20/35/40/45/50W (Default 50W) 2x2: 20/35/40/45/50W (Default 50W) 2x4: 30/40/50/60/72W (Default 72W)
Selectable CCT	30/35/40/50/65K (Default 4000K)
Power Factor	> 0.9
CRI	90+
Lumens	1x4: Up to 6,644 lm 2x2: Up to 6,773 lm 2x4: Up to 9,663 lm
Efficacy	Up to 154 lm/W
Beam Angle	125°
Dimming	0-10V
Mounting	Surface, T-Grid, Suspension
Applications	Office, Conference Rooms, Retail, Commercial Spaces, Healthcare

RENO LIGHTING

All Rights Reserved © Renolighting (905) 604-4666 | sales@renolighting.com | www.renolighting.com
Reno Lighting reserves the right to change this product and related instructions without notice.
Refer to the product page for the latest information.

Specifications - AIM Flat Panel 1x4

Order #	Model	Wattage	Efficacy	Lumens	CCT
R35331	RENO-14BLPL-DV-MW-MCCT-HL-MS	20W	146.1 lm/W	2,850.6 lm	30/35/40/50/6500K
		35W	145.9 lm/W	4,745.1 lm	30/35/40/50/6500K
		40W	145.1 lm/W	5,377.3 lm	30/35/40/50/6500K
		45W	141.3 lm/W	5,936.1 lm	30/35/40/50/6500K
		50W	141.8 lm/W	6,845.9 lm	30/35/40/50/6500K

Specifications - AIM Flat Panel 2x2

Order #	Model	Wattage	Efficacy	Lumens	CCT
R35332	RENO-22BLPL-DV-MW-MCCT-HL-MS	20W	154.2 lm/W	3031.2 lm	30/35/40/50/6500K
		35W	149.8 lm/W	4,944.2 lm	30/35/40/50/6500K
		40W	148.5 lm/W	5,498.6 lm	30/35/40/50/6500K
		45W	145.0 lm/W	6,192.4 lm	30/35/40/50/6500K
		50W	143.6 lm/W	6,997.7 lm	30/35/40/50/6500K

Specifications - AIM Flat Panel 2x4

Order #	Model	Wattage	Efficacy	Lumens	CCT
R35333	RENO-24BLPL-DV-MW-MCCT-HL-MS	30W	145.2 lm/W	4,624.2 lm	30/35/40/50/6500K
		40W	145.5 lm/W	5,565.0 lm	30/35/40/50/6500K
		50W	144.2 lm/W	6,678.3 lm	30/35/40/50/6500K
		60W	139.5 lm/W	7,725.7 lm	30/35/40/50/6500K
		72W	144.6 lm/W	10,246.8 lm	30/35/40/50/6500K

RENO LIGHTING
All Rights Reserved © Renolighting (905) 604-4666 | sales@renolighting.com | www.renolighting.com
Reno Lighting reserves the right to change this product and related instructions without notice.
Refer to the product page for the latest information.

DLC Certification


Order #	Model #	Application	DLC Standard	DLC Premium
R35331	RENO-14BLPL-DV-MW-MCCT-HL-MS	Low-Bay Luminaires for Commercial and Industrial Buildings	S-Y7TYB8	
		1x4 Luminaires for Ambient Lighting of Interior Commercial Spaces		S-GJN3HN
R35332	RENO-22BLPL-DV-MW-MCCT-HL-MS	Low-Bay Luminaires for Commercial and Industrial Buildings	S-DFL7SM	
		2x2 Luminaires for Ambient Lighting of Interior Commercial Spaces		S-6YVQ10
R35333	RENO-24BLPL-DV-MW-MCCT-HL-MS	High-Bay Luminaires for Commercial and Industrial Buildings	S-86TWK9	
		2x4 Luminaires for Ambient Lighting of Interior Commercial Spaces		S-XWXYHK


All Rights Reserved © Renolighting (905) 604-4666 | sales@renolighting.com | www.renolighting.com
Reno Lighting reserves the right to change this product and related instructions without notice.
Refer to the product page for the latest information.

Dimensions


Aim Flat Panel 1x4 | 2x4 | 2x2


R35331- AIM Flat Panel 1x4







R35333- AIM Flat Panel 2x4






R35332- AIM Flat Panel 2x2





All Rights Reserved © Renolighting (905) 604-4666 | sales@renolighting.com | www.renolighting.com
Reno Lighting reserves the right to change this product and related instructions without notice.
Refer to the product page for the latest information.

Accessories
Mounting




1x4 Surface Mount Kit
R39201
RENO-SMK14



2x2 Surface Mount Kit
R39202
RENO-SMK22




2x4 Surface Mount Kit
R39203
RENO-SMK24




1x4 Recessed Flange
R39211
RENO-RFK14



2x2 Recessed Flange
R39212
RENO-RFK22



2x4 Recessed Flange
R39213
RENO-RFK24



10Ft Suspension Kit
R39204
RENO-RP

Order #	Model #	Description
R39201	RENO-SMK14	1 x 4 Surface Mount Frame
R39202	RENO-SMK22	2 x 2 Surface Mount Frame
R39203	RENO-SMK24	2 x 4 Surface Mount Frame
R39211	RENO-RFK14	1 x 4 Recessed Flange Kit
R39212	RENO-RFK22	2 x 2 Recessed Flange Kit
R39213	RENO-RFK24	2 x 4 Recessed Flange Kit
R39204	RENO-RP	10Ft Aircraft Suspension Cable for 1x4, 2x4, 2x2

All Rights Reserved © Renolighting (905) 604-4666 | sales@renolighting.com | www.renolighting.com
Reno Lighting reserves the right to change this product and related instructions without notice.
Refer to the product page for the latest information.


Accessories
Emergency LED Drivers



Emergency LED Driver
R83001
RENO-EM-H15

Order #	Model #	Description
R83001	RENO-EM-H15	External Mount | 15W | 100-347Vac | 50/60Hz | 0.1A max | 12W max | 170V DC | 5°C ~50°C

Accessories
Sensor Remotes



PIR Sensor for the Sensor-Ready Flat Panels
R74006
RENO-SENSOR-PIR-2.5MM-H



Remote Control for Standalone Sensor (with Screen)
R73002
RENO-REMOTE-H



Remote Control for Standalone Sensor (without Screen)
R73005
RENO-REMOTE-H-ECO

Order #	Model #	Type	Description
R74006	RENO-SENSOR-PIR-2.5MM-H	Sensor	PIR Sensor for the Sensor-Ready Flat Panels (R35331 / R35332 / R35333)
R73002	RENO-REMOTE-H	Remote	Remote Control for Standalone Sensors with Screen (Only 1 needed per project)
R73005	RENO-REMOTE-H-ECO	Remote	Remote Control for Standalone sensors without Screen (Only 1 needed per project)


RENO LIGHTING
All Rights Reserved © Renolighting (905) 604-4666 | sales@renolighting.com | www.renolighting.com
Reno Lighting reserves the right to change this product and related instructions without notice.
Refer to the product page for the latest information.

Accessories


RENO SMART NLC Sensors




Bluetooth PIR sensor for the Sensor-Ready Flat Panels
R75005
RENO-RS-JK-2.5MM-PIR-12V



Ceiling Mounted Gateway for RENO Smart NLC System
R75201
RENO-RS-GW-BCNW



5-Key Reset Remote Controller
R75301
RENO-RS-RC-BNNN



7-Key Smart Wall Switch for RENO Smart NLC System
R75302
RENO-RS-RC-BNNG

Order #	Model #	Description
R75005	RENO-RS-JK-2.5MM-PIR-12V	Bluetooth PIR sensor for the Sensor-Ready Flat Panels (R35331 / R35332 / R35333)
R75201	RENO-RS-GW-BCNW	Ceiling Mounted Gateway for RENO Smart NLC System
R75301	RENO-RS-RC-BNNN	5-Key Reset Remote Controller
R75302	RENO-RS-RC-BNNG	7-Key Smart Wall Switch for RENO Smart NLC System

All Rights Reserved © Renolighting (905) 604-4666 | sales@renolighting.com | www.renolighting.com
Reno Lighting reserves the right to change this product and related instructions without notice.
Refer to the product page for the latest information.