

Date		Project	
Type		Part Number	



ALL-IN-ONE PERFORMANCE LIGHTING

DECO Series

Double Ring Ceiling Light with Sensor

The DECO Series ceiling light features a sleek double-ring design with energy-efficient LED technology, providing bright and uniform illumination. It includes a built-in microwave sensor for automatic motion detection, enabling hands-free operation and improved energy savings. The sensor is discreetly integrated for a seamless look, making it ideal for residential or commercial spaces such as hallways, offices, or entrances. Designed for durability and convenience, it offers adjustable sensitivity and lighting duration settings to suit various needs.



PRODUCT FEATURES

- ETL/FCC Certified
- Built-in Microwave Sensor (Remote Required to Customize Settings)
- 120V TRIAC Dimming
- Operating temperature: -4°F to +104°F (-20°C to +40°C)
- IP20 Rated Damp location
- Frosted Polycarbonate Lens
- Brushed Nickel (Stainless Steel) Finish
- Installation height: 3 meter
- Detection area: 2-5 meter
- Rated Lifespan: L70 ~50,000 hrs
- 10 year limited warranty

KEY SPECIFICATIONS

Voltage	120V
Wattage	Selectable Wattages 12" - 8/12/16W 14" - 12/16/22W 16" - 16/22/30W
Size	12", 14", 16"
Power Factor	>0.9
CCT	27/30/35/40/5000K
CRI	>80
Efficacy	85lm/W
Lumens	680 – 2,550 lm
Beam Angle	120°
Dimming	120V TRIAC
Mounting	Ceiling, Wall
Applications	Commercial, Residential, Multi-Res



SPECIFICATIONS – 12” MULTI POWER (8/12/16W)

Order#	Model	Wattage	Voltage	Lumens	Efficacy	CCT
R31032	RENO-CLD-12”-BN-MW-MCCT-MS-G2	8W	120V	680 lm	85 lm/W	2700K
				680 lm	85 lm/W	3000K
				680 lm	85 lm/W	3500K
				680 lm	85 lm/W	4000K
				680 lm	85 lm/W	5000K
		12W	120V	1,020 lm	85 lm/W	2700K
				1,020 lm	85 lm/W	3000K
				1,020 lm	85 lm/W	3500K
				1,020 lm	85 lm/W	4000K
				1,020 lm	85 lm/W	5000K
		16W	120V	1,360 lm	85 lm/W	2700K
				1,360 lm	85 lm/W	3000K
				1,360 lm	85 lm/W	3500K
				1,360 lm	85 lm/W	4000K
				1,360 lm	85 lm/W	5000K


SPECIFICATIONS – 14” MULTI POWER (12/16/22W)

Order#	Model	Wattage	Voltage	Lumens	Efficacy	CCT
R31033	RENO-CLD-14”-BN-MW-MCCT-MS-G2	12W	120V	935 lm	85 lm/W	2700K
				935 lm	85 lm/W	3000K
				935 lm	85 lm/W	3500K
				935 lm	85 lm/W	4000K
				935 lm	85 lm/W	5000K
		16W	120V	1,400 lm	85 lm/W	2700K
				1,400 lm	85 lm/W	3000K
				1,400 lm	85 lm/W	3500K
				1,400 lm	85 lm/W	4000K
				1,400 lm	85 lm/W	5000K
		22W	120V	1,870 lm	85 lm/W	2700K
				1,870 lm	85 lm/W	3000K
				1,870 lm	85 lm/W	3500K
				1,870 lm	85 lm/W	4000K
				1,870 lm	85 lm/W	5000K

SPECIFICATIONS – 16" MULTI POWER (16/22/30W)

Order#	Model	Wattage	Voltage	Lumens	Efficacy	CCT
R31034	RENO-CLD-16"-BN-MW-MCCT-MS-G2	16W	120V	1,275 lm	85 lm/W	2700K
				1,275 lm	85 lm/W	3000K
				1,275 lm	85 lm/W	3500K
				1,275 lm	85 lm/W	4000K
				1,275 lm	85 lm/W	5000K
		22W	120V	1,900 lm	85 lm/W	2700K
				1,900 lm	85 lm/W	3000K
				1,900 lm	85 lm/W	3500K
				1,900 lm	85 lm/W	4000K
				1,900 lm	85 lm/W	5000K
		30W	120V	2,550 lm	85 lm/W	2700K
				2,550 lm	85 lm/W	3000K
				2,550 lm	85 lm/W	3500K
				2,550 lm	85 lm/W	4000K
				2,550 lm	85 lm/W	5000K

ACCESSORIES – REMOTE



R73004
RENO-REMOTE-M
Remote for DECO and LUMA
series fixtures

Order#	Model	Description
R73004	RENO-REMOTE-M	Remote for DECO and LUMA series fixtures

DIMENSIONS

