

Date		Project	
Type		Part Number	



ALL-IN-ONE PERFORMANCE LIGHTING

EMERGENCY Series

Emergency Battery

These battery units are designed with a rugged metal frame and sporting double swivel positioning heads on top to provide bright illumination. Easy knockouts provided for swift installation on each jobsite.



PRODUCT FEATURES

- UL 924 Listed for Damp Locations
- Meets NFPA 101 Life Safety Code, NEC, OSHA
- CSA C22.2 No. 141-15 performance certified
- UL-94-V0 flame-retardant, fire-resistant
- Maintenance-free 12V Sealed Lead-acid battery
- 18 Gauge steel housing
- 150W at 30mins battery backup time
- Operating Temperature: 32°F - 104°F (0°C - 40°C)
- 5 year warranty

KEY SPECIFICATIONS

Input Voltage	120/277/347V
Output Voltage	12VDC
Head Wattage	2 x 5W
Power	150W
Recharge Time	24 Hours
Discharge Time	30 Minutes
Applications	Commercial, Warehouse, Retail Facilities



SPECIFICATIONS

Order#	Model	Wattage	Head Power	Discharge Time	Input Voltage	Output Voltage
R61204	RENO-EBP150W-U	150W	2 x 5W	30 Minutes	120/277/347V	12V

ACCESSORIES – REMOTE HEADS



R61101
RENO-ERH2W-1
Single Head Emergency Light



R61106
RENO-ERH5W-1
Single Head Emergency Light



R61105
RENO-ERH5W-2
Double Head Emergency Light

Order#	Model	Description
R61101	RENO-ERH2W-1	Single Head Emergency Light 2W
R61106	RENO-ERH5W-1	Single Head Emergency Light 5W
R61105	RENO-ERH5W-2	Double Head Emergency Light 2 x 5W

DIMENSIONS

