

|             |  |                    |  |
|-------------|--|--------------------|--|
| <b>Date</b> |  | <b>Project</b>     |  |
| <b>Type</b> |  | <b>Part Number</b> |  |



ALL-IN-ONE PERFORMANCE LIGHTING

# ZENITH Series

## Linear Highbay

The Zenith Series PRIME LED Linear Highbay is our flagship commercial/industrial fixture. Engineered with All-In-One features including Multi Power, Multi CCT, and Dual Voltage, alongside Emergency Backup, Standalone Sensor, and RENO Smart Sensor NLC compatibilities, they are the sleek and lightweight lighting solution for businesses looking to reduce operational costs while enhancing sustainability.



## PRODUCT FEATURES

- DLC Premium
- 0-10V dimming control compatible
- Semi-frosted PMMA lens
- Powder-Coated Steel Body (White)
- Shipped with V-Hooks, Chain & 10 ft cord
- Operating temperature: -40°F to +122°F (-40°C to +50°C)
- Damp location suitable
- Rated Lifespan: L70 ~100,000 hrs
- 10kVA surge protection
- 10 year warranty


 EMERGENCY  
 BACKUP READY

 RENO SMART  
 NLC SYSTEM

 STANDALONE  
 SENSOR OPTIONS

## KEY SPECIFICATIONS

|                     |   |
|---------------------|---|
| <b>Voltage</b>      | 120-347V  |
| <b>Wattage</b>      | <b>Selectable Wattage</b><br><b>R1</b> - 100/125/140W<br><b>R2</b> - 145/155/175W<br><b>R3</b> - 180/210/230W<br><b>R4</b> - 250/300/340W<br><b>R5</b> - 340/380/420/450W |
| <b>CCT</b>          | 3500K, 4000K, 5000K   |
| <b>Efficacy</b>     | 160 - 177 lm/W  |
| <b>Lumens</b>       | 17,000 – 76,500 lm  |
| <b>CRI</b>          | >80   |
| <b>Power Factor</b> | >0.9  |
| <b>Beam Angle</b>   | 120°  |
| <b>Dimming</b>      | 0-10V   |
| <b>Mounting</b>     | Surface, Pendant, Suspended   |
| <b>Applications</b> | Commercial, Industrial, Retail Facilities   |

## SPECIFICATIONS – R1 MULTI POWER (100/125/140W)

| Order# | Model                   | Wattage | Voltage  | Lumens    | Efficacy   | CCT   |
|--------|-------------------------|---------|----------|-----------|------------|-------|
| R34111 | RENO-LHB2-DV-MW-MCCT-R1 | 100W    | 120-347V | 17,000 lm | 170 lm/W   | 3500K |
|        |                         |         |          | 17,700 lm | 177 lm/W   | 4000K |
|        |                         |         |          | 17,100 lm | 171 lm/W   | 5000K |
|        |                         | 125W    | 120-347V | 20,625 lm | 165 lm/W   | 3500K |
|        |                         |         |          | 21,625 lm | 173 lm/W   | 4000K |
|        |                         |         |          | 20,750 lm | 166 lm/W   | 5000K |
|        |                         | 140W    | 120-347V | 22,470 lm | 160.5 lm/W | 3500K |
|        |                         |         |          | 23,800 lm | 170 lm/W   | 4000K |
|        |                         |         |          | 22,540 lm | 161 lm/W   | 5000K |

## SPECIFICATIONS – R2 MULTI POWER (145/155/175W)

| Order# | Model                   | Wattage | Voltage  | Lumens    | Efficacy   | CCT   |
|--------|-------------------------|---------|----------|-----------|------------|-------|
| R34112 | RENO-LHB2-DV-MW-MCCT-R2 | 145W    | 120-347V | 23,940 lm | 171 lm/W   | 3500K |
|        |                         |         |          | 24,780 lm | 177 lm/W   | 4000K |
|        |                         |         |          | 24,080 lm | 172 lm/W   | 5000K |
|        |                         | 155W    | 120-347V | 25,885 lm | 167 lm/W   | 3500K |
|        |                         |         |          | 27,125 lm | 175 lm/W   | 4000K |
|        |                         |         |          | 26,040 lm | 168 lm/W   | 5000K |
|        |                         | 175W    | 120-347V | 28,560 lm | 163.2 lm/W | 3500K |
|        |                         |         |          | 30,275 lm | 173 lm/W   | 4000K |
|        |                         |         |          | 28,700 lm | 164 lm/W   | 5000K |

## SPECIFICATIONS – R3 MULTI POWER (180/210/230W)

| Order# | Model                   | Wattage | Voltage  | Lumens    | Efficacy   | CCT   |
|--------|-------------------------|---------|----------|-----------|------------|-------|
| R34113 | RENO-LHB2-DV-MW-MCCT-R3 | 180W    | 120-347V | 29,700 lm | 165 lm/W   | 3500K |
|        |                         |         |          | 31,500 lm | 175 lm/W   | 4000K |
|        |                         |         |          | 29,880 lm | 166 lm/W   | 5000K |
|        |                         | 210W    | 120-347V | 34,440 lm | 164 lm/W   | 3500K |
|        |                         |         |          | 36,540 lm | 175 lm/W   | 4000K |
|        |                         |         |          | 34,650 lm | 165 lm/W   | 5000K |
|        |                         | 230W    | 120-347V | 37,605 lm | 163.5 lm/W | 3500K |
|        |                         |         |          | 39,790 lm | 173 lm/W   | 4000K |
|        |                         |         |          | 37,720 lm | 164 lm/W   | 5000K |

## SPECIFICATIONS – R4 MULTI POWER (250/300/340W)

| Order# | Model                   | Wattage | Voltage  | Lumens    | Efficacy   | CCT   |
|--------|-------------------------|---------|----------|-----------|------------|-------|
| R34114 | RENO-LHB2-DV-MW-MCCT-R4 | 250W    | 120-347V | 43,000 lm | 172 lm/W   | 3500K |
|        |                         |         |          | 45,500 lm | 182 lm/W   | 4000K |
|        |                         |         |          | 44,250 lm | 177 lm/W   | 5000K |
|        |                         | 300W    | 120-347V | 50,400 lm | 168 lm/W   | 3500K |
|        |                         |         |          | 53,400 lm | 178 lm/W   | 4000K |
|        |                         |         |          | 51,900 lm | 173 lm/W   | 5000K |
|        |                         | 340W    | 120-347V | 55,998 lm | 164.7 lm/W | 3500K |
|        |                         |         |          | 59,840 lm | 176 lm/W   | 4000K |
|        |                         |         |          | 57,800 lm | 170 lm/W   | 5000K |


## SPECIFICATIONS – R5 MULTI POWER (340/380/420/450W)

| Order# | Model                   | Wattage | Voltage  | Lumens    | Efficacy   | CCT   |
|--------|-------------------------|---------|----------|-----------|------------|-------|
| R34115 | RENO-LHB4-DV-MW-MCCT-R5 | 340W    | 120-347V | 56,100 lm | 165 lm/W   | 3500K |
|        |                         |         |          | 58,820 lm | 173 lm/W   | 4000K |
|        |                         |         |          | 56,440 lm | 166 lm/W   | 5000K |
|        |                         | 380W    | 120-347V | 62,320 lm | 164 lm/W   | 3500K |
|        |                         |         |          | 65,360 lm | 172 lm/W   | 4000K |
|        |                         |         |          | 62,700 lm | 165 lm/W   | 5000K |
|        |                         | 420W    | 120-347V | 68,460 lm | 163 lm/W   | 3500K |
|        |                         |         |          | 71,820 lm | 171 lm/W   | 4000K |
|        |                         |         |          | 68,880 lm | 164 lm/W   | 5000K |
|        |                         | 450W    | 120-347V | 72,810 lm | 161.8 lm/W | 3500K |
|        |                         |         |          | 76,500 lm | 170 lm/W   | 4000K |
|        |                         |         |          | 73,350 lm | 163 lm/W   | 5000K |


## DLC CERTIFICATION

| Order# | Model                   | Application   | DLC Standard | DLC Premium |
|--------|-------------------------|---|--------------|-------------|
| R34111 | RENO-LHB2-DV-MW-MCCT-R1 | High-Bay Luminaires for Commercial and Industrial Buildings | –            | S-Y5GG1D    |
| R34112 | RENO-LHB2-DV-MW-MCCT-R2 | High-Bay Luminaires for Commercial and Industrial Buildings | –            | S-PPJLMR    |
| R34113 | RENO-LHB2-DV-MW-MCCT-R3 | High-Bay Luminaires for Commercial and Industrial Buildings | –            | S-5KS9TJ    |
| R34114 | RENO-LHB2-DV-MW-MCCT-R4 | High-Bay Luminaires for Commercial and Industrial Buildings | –            | S-XGXWC8    |
| R34115 | RENO-LHB4-DV-MW-MCCT-R5 | High-Bay Luminaires for Commercial and Industrial Buildings | –            | S-7L43NZ    |


## ACCESSORIES – MOUNTING




R39301  
RENO-LHB-HPM  
Center box for pendant  
mounting R1




R39305  
RENO-LHB-CK-R1  
Connection Kit for ganging  
Highbays R1




R39306  
RENO-LHB-CK-R2/R3  
Connection Kit for ganging  
Highbays R2/R3



R39303  
RENO-LHB-WG-R1  
Wire guards for linear  
Highbays R1



R39304  
RENO-LHB-WG-R2  
Wire guards for linear  
Highbays R2



R39308  
RENO-LHB-WG-R3  
Wire guards for linear  
Highbays R3

| Order# | Model             | Description                               |
|--------|-------------------|---|
| R39301 | RENO-LBH-HPM      | Center box for pendant mounting R1        |
| R39305 | RENO-LHB-CK-R1    | Connection Kit for ganging Highbays R1    |
| R39306 | RENO-LHB-CK-R2/R3 | Connection Kit for ganging Highbays R2/R3 |
| R39303 | RENO-LHB-WG-R1    | Wire guards for linear Highbays R1        |
| R39304 | RENO-LHB-WG-R2    | Wire guards for linear Highbays R2        |
| R39308 | RENO-LHB-WG-R3    | Wire guards for linear Highbays R3        |


## ACCESSORIES – RENO SMART NLC SENSORS




R75001  
RENO-RS-JK-BPDN-12V  
Bluetooth 3.5mm Jack PIR  
Sensor for RENO Smart NLC  
System



R75002  
RENO-RS-JK-BMWM-12V  
Bluetooth 3.5mm Jack  
Microwave Sensor for RENO  
Smart NLC System



R75201  
RENO-RS-GW-BCNW  
Ceiling Mounted Gateway for  
RENO Smart NLC System




R75302  
RENO-RS-RC-BNNG  
7-Key Smart Wall Switch for  
RENO Smart NLC System



R75301  
RENO-RS-RC-BNNG  
5-Key Reset Remote Controller

| Order# | Model               | Description   |
|--------|---------------------|---|
| R75001 | RENO-RS-JK-BPDN-12V | Bluetooth 3.5mm Jack PIR Sensor for RENO Smart NLC System       |
| R75002 | RENO-RS-JK-BMWM-12V | Bluetooth 3.5mm Jack Microwave Sensor for RENO Smart NLC System |
| R75201 | RENO-RS-GW-BCNW     | Ceiling Mounted Gateway for RENO Smart NLC System               |
| R75302 | RENO-RS-RC-BNNG     | 7-Key Smart Wall Switch for RENO Smart NLC System               |
| R75301 | RENO-RS-RC-BNNG     | 5-Key Reset Remote Controller                                   |

## ACCESSORIES – EMERGENCY LED DRIVERS



R83002  
RENO-EM-H25  
Emergency LED Driver  
(100-347V AC, 50-60Hz, 25W)

R83003  
RENO-EM-H40 (with test switch)  
Emergency LED Driver  
(100-347V AC, 50-60Hz, 40W)

| Order# | Model       | Description   |
|--------|-------------|---|
| R83002 | RENO-EM-H25 | Emergency LED Driver (100-347V AC, 50-60Hz, 25W)                    |
| R83003 | RENO-EM-H40 | Emergency LED Driver (100-347V AC, 50-60Hz, 25W) - with test switch |

## ACCESSORIES – STANDALONE SENSOR & REMOTES



R71002  
RENO-SENSOR-MW-H  
Bi-level dim sensor for linear  
Highbays

R74004  
RENO-SENSOR-PIR3.5-PH15M  
Long Detection Range PIR  
Sensor


R73002  
RENO-REMOTE-H  
Remote Control for Standalone  
Sensors (With Screen)

R73005  
RENO-REMOTE-H-ECO  
Remote Control for Standalone  
sensors (Without Screen)

| Order# | Model                    | Description   |
|--------|--------------------------|---|
| R71002 | RENO-SENSOR-MW-H         | Bi-level dim sensor for linear Highbays   |
| R74004 | RENO-SENSOR-PIR3.5-PH15M | Long Detection Range PIR Sensor   |
| R73002 | RENO-REMOTE-H            | Remote Control for Standalone Sensors (With Screen)<br>Note: Only 1 needed per project.   |
| R73005 | RENO-REMOTE-H-ECO        | Remote Control for Standalone sensors (Without Screen)<br>Note: Only 1 needed per project |


## DIMENSIONS

**R1 - RENO-LHB2-DV-MW-MCCT-R1**




Width: 14.6" (370.8 mm)  
 Height: 2.0" (50.8 mm)  
 Length: 25.5" (647.7 mm)  
 Weight: 11 lbs (4.98 kg)

**R2 - RENO-LHB2-DV-MW-MCCT-R2**




Width: 18.5" (470 mm)  
 Height: 2.0" (50.8 mm)  
 Length: 25.5" (647.7 mm)  
 Weight: 15 lbs (6.80 kg)

**R3 - RENO-LHB2-DV-MW-MCCT-R3**  
**R4 - RENO-LHB2-DV-MW-MCCT-R4**



Width: 23.5" (597 mm)  
 Height: 2.0" (50.8 mm)  
 Length: 25.5" (647.7 mm)  
 Weight: 19 lbs (8.62 kg)

**R5 - RENO-LHB4-DV-MW-MCCT-R5**



Width: 23.5" (597 mm)  
 Height: 2.0" (50.8 mm)  
 Length: 48" (1,219.2 mm)  
 Weight: 48 lbs (21.77 kg)