

Date		Project	
Type		Part Number	


 THE EVERYDAY COMPETITIVE OPTION

TYPE A T8

Type A T8 Tube

Make the switch to T8 Type A LED lamps for an effortless upgrade from fluorescent tubes to modern, energy-saving LED technology. Designed for plug-and-play compatibility with existing electronic ballasts, this LED tube offers instant brightness, reduced energy consumption, and a long lifespan of up to 50,000 hours. Perfect for offices, schools, hospitals, retail spaces, and warehouses, it provides uniform, flicker-free lighting with excellent color clarity.



PRODUCT FEATURES

- Direct plug-in & Safe Installation
- No UV or IR radiation
- High luminous efficiency
- Compatible with instant & programmed start ballast
- Operating temperature: -4°F to +113°F (-20°C to +45°C)
- Rated Lifetime L70(hrs): >50,000
- 5 year warranty

KEY SPECIFICATIONS

Lamp Base	G13
Size	4.0 ft
Wattage	11W or 14W
Voltage	BF
CCT	3500K or 4000K or 5000K
Lumens	Up to 2,200 lm
CRI	>83
Beam Angle	330°
Lifespan	50,000 hrs
Dimming	n/a




SPECIFICATIONS

Order#	Model	Size	Wattage	Voltage	CCT	Lumens	Beam Angle
R41030	WLL-LEDT8BC11/835-ECO	4.0 ft	11W	BF	3500K	1,750 lm	320°
R41031	WLL-LEDT8BC11/840-ECO	4.0 ft	11W	BF	4000K	1,800 lm	320°
R41032	WLL-LEDT8BC11/850-ECO	4.0 ft	11W	BF	5000K	1,800 lm	320°
R41033	WLL-LEDT8BC14/840-ECO	4.0 ft	14W	BF	4000K	2,200 lm	320°
R41034	WLL-LEDT8BC14/850-ECO	4.0 ft	14W	BF	5000K	2,200 lm	320°

DLC CERTIFICATION

Order#	Model	Application	DLC Standard	DLC Premium
R41030	WLL-LEDT8BC11/835-ECO	Replacement Lamps	S-LPHCI1	–
R41031	WLL-LEDT8BC11/840-ECO	Replacement Lamps	S-AG2930	–
R41032	WLL-LEDT8BC11/850-ECO	Replacement Lamps	S-27RQM1	–
R41033	WLL-LEDT8BC14/840-ECO	Replacement Lamps	S-6LZTRK	–
R41034	WLL-LEDT8BC14/850-ECO	Replacement Lamps	S-Y8REKX	–

ACCESSORIES – MOUNTING




RENO-S-SN-U-PBT
Low profile rotary lock
T8 socket

Model	Description
RENO-S-SN-U-PBT	Low profile rotary lock T8 socket

DIMENSIONS

4 FT



Full Body Width: 47.2" (1198.9 mm)

Lit Width: 44.7" (1135.4 mm)

Thickness: 1.0" (25.4 mm)