

Issued: 2023-06.06

ID#: 160623

DarkSky Approved Luminaire

DarkSky International grants this approval to:

RENO LED LIGHTING

for achieving certification of the following DarkSky friendly product family:

RENO-SB-100W/150W

Thank you for your part in the world-wide effort to protect and preserve the natural nighttime environment and our heritage of dark skies.

James Brigagliano
Lighting Program Manager



DARKSKY APPROVED

Reduces light pollution Certified by DarkSky.org Ruskin K. Hartley
DarkSky Executive Director




| Date: | Project Name: | |
|-------|---------------|--|
| Туре: | Part Number: | |





ARIES SERIES LED FLOOD LIGHT/SHOE BOX



DESCRIPTION

RENO Flood/Area Light is constructed with a durable, die-cast aluminum housing and PMMA optic lens (prevent yellowing) is the perfect lighting solution for your parking lot, street, walkway, building. Energy savings can be as much as 85% while eliminating maintenance costs in labor and lamp and ballast replacement. Designed for pole or wall-mounting with either an arm extension, slip fitter, U-bracket or trunnion mount.

FEATURES

- **DLC Premium**
- Dark Sky Rated When Selected 3K Only
- IP66 Rated
- Built-in 10KV Surge Protection
- Optional Plug-In Dimming sensor
- Type III Standard, Type II ,IV & V available
- Rated Lifetime L90(hrs): >70,000
- Input line voltage: 120-347V
- Custom colours available
- Multi Wattage
- Powder-coated Black
- 10 year warranty

APPLICATIONS



Building



Outdoor parking



Street



Walkway

























| Date: | Project Name: |
|-------|---------------|
| Туре: | Part Number: |

SPECIFICATION

| ORDER# | MODEL# | WATTS | VOLTAGE (V) | LUMENS | HOURS RATING | CCT(K) |
|--------|----------------------------|------------------|----------------|---------------------------------|-----------------|--------|
| R53021 | RENO-SB-100W-MW-DV-MCCT-R1 | 40/60/80/100W | 120-347V | 6000/9000/ 12,000/15,000 | 70,000 | 3000K |
| R53022 | RENO-SB-150W-MW-DV-MCCT-R2 | 100/120/135/150W | 120-347V | 15,000/18,000/ 20,250/22,500 | 70,000 | 3000K |
| R53023 | RENO-SB-240W-MW-DV-MCCT-R3 | 180/200/220/240W | 120-347V | 27,000/30,000/ 33,000/36,000 | 70,000 | 3000K |
| R53024 | RENO-SB-320W-MW-DV-MCCT-R4 | 240/280/300/320W | 120-347V | 36,000/42,000/ 45,000/48,000 | 70,000 | 3000K |

ACCESSORIES

| ORDER# | MODEL# | DESCRIPTION |
|--------|-----------------------|---|
| R59004 | RENO-Trunnion-G3 | U Bracket for Shoebox G3 |
| R59005 | RENO-Slip Fitter-G3 | Slip Fitter for Shoebox G3 |
| R59006 | RENO-STRAIGHT ARM-G3 | Straight Arm mount for Shoebox G3 |
| R59010 | RENO-SB-SHIELD-R1 | Shoebox Shield for 75W/100W/150W |
| R59011 | RENO-SB-SHIELD-R2 | Shoebox Shield for 240W-320W |
| R59202 | RENO-SB-TYPE-II-R1/R2 | Distribution optics lens for R1/R2 Shoebox |
| R59203 | RENO-SB-TYPE-II-R3/R4 | Distribution optics lens for R3/R4 Shoebox (2pcs) |
| R59204 | RENO-SB-TYPE-IV-R1/R2 | Distribution Optics Lens for R1/R2 Shoebox |
| R59205 | RENO-SB-TYPE-IV-R3/R4 | Distribution optics lens for R3/R4 Shoebox (2pcs) |

SENSOR OPTIONS

| ORDER# | MODEL# | DESCRIPTION |
|--------|------------------|--------------------------|
| R72001 | RENO-SENSOR-PC-S | Photocell Sensor |
| R71002 | RENO-SENSOR-MW-H | Dimming Microwave Sensor |






| Date: | Project Name: |
|-------|---------------|
| Туре: | Part Number: |

REMOTE OPTIONS

| ORDER# | MODEL# | DESCRIPTION |
|--------|---------------|----------------|
| R73002 | RENO-REMOTE-H | Remote Control |

DIMENSIONS





MOUNTING OPTIONS

304.8mm

(12")





86.4mm

(3.4")