


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:120.4V I:0.2267A P:27.22W PF:0.9973 Lamp Flux:3878.78x1 lm		
NAME: MLSN4-28/D10/U/35	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:1182*66*14mm	PROTECTION ANGLE:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 142.48 lm/W			
MODEL	3500K	I _{max} (cd)	1272	S/MH(C0/180)	1.19
NOMINAL POWER(W)	28	LOR(%)	100.0	S/MH(C90/270)	1.26
RATED VOLTAGE(V)	120-277	TOTAL FLUX(lm)	3878.8	η UP,DN(C0-180)	0.0,50.2
NOMINAL FLUX(lm)	3878.78	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.0,49.8
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	120	η down(%)	100.0	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2020-06-16

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity:65.0%
Test Distance:8.900m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	Φ lum, lamp
5	1263	1249	1245	1249	1264	1250	1247	1250	0- 5	30.09	30.09	0.78,0.78
10	1240	1219	1219	1220	1241	1221	1221	1220	5- 10	88.46	118.6	3.06,3.06
15	1201	1182	1192	1183	1203	1186	1196	1185	10- 15	143.0	261.6	6.74,6.74
20	1149	1140	1166	1141	1152	1144	1171	1143	15- 20	192.5	454.1	11.7,11.7
25	1083	1092	1140	1093	1087	1097	1146	1097	20- 25	235.8	689.8	17.8,17.8
30	1007	1042	1078	1042	1012	1046	1081	1046	25- 30	271.0	960.8	24.8,24.8
35	922.5	979.0	1017	979.3	927.9	982.5	1015	983.3	30- 35	295.7	1256	32.4,32.4
40	832.5	897.5	955.9	899.3	838.4	899.6	949.5	898.6	35- 40	310.5	1567	40.4,40.4
45	738.0	816.8	894.7	819.9	745.0	816.8	883.8	815.5	40- 45	316.1	1883	48.5,48.5
50	641.0	737.5	833.4	741.4	649.2	735.6	818.2	734.6	45- 50	313.2	2196	56.6,56.6
55	545.5	660.6	763.4	666.1	553.2	658.3	745.1	656.2	50- 55	302.6	2499	64.4,64.4
60	449.5	586.1	693.3	592.9	457.8	582.8	671.9	580.3	55- 60	284.4	2783	71.8,71.8
65	355.6	507.9	623.2	513.7	364.9	501.9	598.8	500.2	60- 65	260.3	3044	78.5,78.5
70	264.5	433.2	553.2	438.2	273.7	425.0	525.6	424.0	65- 70	231.3	3275	84.4,84.4
75	177.7	362.8	483.1	366.9	185.9	352.1	452.5	351.9	70- 75	199.0	3474	89.6,89.6
80	98.65	297.2	418.3	299.7	107.6	284.7	393.2	285.5	75- 80	165.5	3639	93.8,93.8
85	38.05	241.0	353.6	238.6	45.94	231.6	333.9	232.3	80- 85	134.0	3773	97.3,97.3
90	11.78	187.4	288.8	180.2	17.41	180.9	274.7	181.8	85- 90	105.4	3879	100,100
95									90- 95			
100									95-100			
105									100-105			
110									105-110			
115									110-115			
120									115-120			
125									120-125			
130									125-130			
135									130-135			
140									135-140			
145									140-145			
150									145-150			
155									150-155			
160									155-160			
165									160-165			
170									165-170			
175									170-175			
180									175-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		


C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2020-06-16

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
 Humidity:65.0%
 Test Distance:8.900m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:120.4V I:0.2267A P:27.22W PF:0.9973 Lamp Flux:3878.78x1 lm		
NAME: MLSN4-28/D10/U/35	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:1182*66*14mm	PROTECTION ANGLE:

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	.00
1.0	1.01	.96	.91	.99	.94	.90	.94	.90	.87	.90	.87	.84	.87	.84	.82	.79
2.0	.87	.79	.73	.85	.78	.72	.81	.75	.70	.78	.73	.69	.75	.71	.67	.65
3.0	.76	.67	.60	.74	.66	.59	.71	.64	.58	.68	.62	.57	.66	.61	.56	.54
4.0	.67	.58	.50	.66	.57	.50	.63	.55	.49	.61	.54	.49	.58	.53	.48	.46
5.0	.60	.50	.43	.59	.50	.43	.56	.49	.42	.54	.47	.42	.52	.46	.42	.39
6.0	.54	.44	.38	.53	.44	.37	.51	.43	.37	.49	.42	.37	.48	.41	.36	.34
7.0	.49	.40	.33	.48	.39	.33	.46	.38	.33	.45	.38	.33	.43	.37	.32	.30
8.0	.44	.36	.30	.44	.35	.29	.42	.35	.29	.41	.34	.29	.40	.34	.29	.27
9.0	.41	.32	.27	.40	.32	.27	.39	.32	.26	.38	.31	.26	.37	.31	.26	.24
10.0	.38	.30	.24	.37	.29	.24	.36	.29	.24	.35	.28	.24	.34	.28	.24	.22



C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: DAMIN
 Test Date: 2020-06-16

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.290
 Humidity: 65.0%
 Test Distance: 8.900m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:120.4V I:0.2267A P:27.22W PF:0.9973 Lamp Flux:3878.78x1 lm					
NAME: MLSN4-28/D10/U/35			TYPE:LED		WEIGHT:
SPEC.:			DIM.:		SERIAL No.:
MFR.:			SUR.:1182*66*14mm		PROTECTION ANGLE:

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.367	.209	.066	.360	.205	.065	.346	.199	.063	.334	.192	.062	.322	.187	.060	
2.0	.325	.178	.055	.319	.175	.054	.307	.170	.053	.295	.166	.052	.285	.161	.051	
3.0	.292	.155	.047	.286	.153	.046	.276	.149	.045	.266	.146	.045	.257	.142	.044	
4.0	.265	.138	.040	.260	.136	.040	.250	.133	.040	.242	.130	.039	.234	.127	.039	
5.0	.242	.123	.036	.237	.122	.036	.229	.119	.035	.221	.117	.035	.214	.114	.034	
6.0	.222	.111	.032	.218	.110	.032	.211	.108	.031	.204	.106	.031	.198	.104	.031	
7.0	.206	.102	.029	.202	.101	.029	.196	.099	.028	.189	.097	.028	.184	.095	.028	
8.0	.191	.093	.026	.188	.093	.026	.182	.091	.026	.177	.089	.026	.171	.088	.026	
9.0	.178	.086	.024	.176	.086	.024	.170	.084	.024	.165	.083	.024	.161	.082	.024	
10.0	.167	.080	.022	.165	.080	.022	.160	.078	.022	.156	.077	.022	.151	.076	.022	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.184	.156	.130	.158	.134	.112	.108	.092	.077	.062	.053	.045	.020	.017	.015	
2.0	.177	.132	.094	.151	.113	.081	.104	.078	.057	.060	.046	.033	.019	.015	.011	
3.0	.169	.114	.071	.145	.099	.062	.099	.069	.043	.057	.040	.026	.018	.013	.008	
4.0	.161	.101	.056	.138	.088	.049	.095	.061	.034	.055	.036	.020	.018	.012	.007	
5.0	.153	.091	.045	.131	.079	.040	.090	.055	.028	.052	.032	.017	.017	.011	.005	
6.0	.145	.083	.038	.125	.072	.033	.086	.050	.023	.050	.029	.014	.016	.010	.005	
7.0	.138	.076	.032	.119	.066	.028	.082	.046	.020	.048	.027	.012	.015	.009	.004	
8.0	.131	.070	.028	.113	.061	.024	.078	.043	.017	.045	.025	.010	.015	.008	.003	
9.0	.125	.065	.025	.108	.056	.022	.075	.040	.015	.043	.023	.009	.014	.008	.003	
10.0	.119	.061	.022	.103	.053	.019	.071	.037	.014	.041	.022	.008	.013	.007	.003	

C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2020-06-16

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
 Humidity:65.0%
 Test Distance:8.900m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:120.4V I:0.2267A P:27.22W PF:0.9973 Lamp Flux:3878.78x1 lm											
NAME: MLSN4-28/D10/U/35					TYPE:LED			WEIGHT:			
SPEC.:					DIM.:			SERIAL No.:			
MFR.:					SUR.:1182*66*14mm			PROTECTION ANGLE:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise				Viewed endwise					
x = 2H y = 2H	16.4	18.0	16.7	18.2	18.4	18.2	19.8	18.5	20.0	20.3	
	3H	17.7	19.2	18.0	19.5	19.7	20.6	22.1	20.9	22.3	22.5
	4H	18.2	19.7	18.6	19.9	20.2	21.8	23.2	22.1	23.5	23.8
	6H	18.6	19.9	18.9	20.2	20.5	23.2	24.5	23.5	24.8	25.1
	8H	18.6	19.9	19.0	20.2	20.5	23.9	25.2	24.2	25.5	25.8
	12H	18.7	19.9	19.0	20.2	20.5	24.7	26.0	25.1	26.3	26.6
4H	2H	17.4	18.8	17.7	19.1	19.4	18.8	20.2	19.1	20.5	20.7
	3H	19.0	20.3	19.4	20.6	20.9	21.4	22.6	21.7	22.9	23.2
	4H	19.7	20.9	20.1	21.2	21.5	22.8	24.0	23.2	24.3	24.6
	6H	20.2	21.2	20.6	21.6	22.0	24.4	25.4	24.8	25.8	26.2
	8H	20.3	21.3	20.8	21.7	22.1	25.2	26.2	25.7	26.6	27.0
	12H	20.4	21.3	20.9	21.7	22.1	26.2	27.1	26.6	27.5	27.9
8H	4H	20.6	21.6	21.0	21.9	22.3	23.1	24.1	23.6	24.5	24.9
	6H	21.4	22.2	21.9	22.6	23.1	25.0	25.8	25.4	26.2	26.7
	8H	21.7	22.5	22.2	22.9	23.4	26.1	26.8	26.5	27.2	27.7
	12H	22.0	22.6	22.5	23.1	23.6	27.3	28.0	27.8	28.4	28.9
12H	4H	20.8	21.8	21.3	22.1	22.6	23.2	24.1	23.6	24.5	24.9
	6H	21.9	22.6	22.3	23.0	23.5	25.1	25.9	25.6	26.3	26.7
	8H	22.4	23.0	22.8	23.5	23.9	26.3	26.9	26.8	27.4	27.9
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.1					+ 0.1 / - 0.1					
1.5H	+ 0.2 / - 0.2					+ 0.2 / - 0.3					
2.0H	+ 0.1 / - 0.3					+ 0.2 / - 0.4					

CIE Pub.117 Corrected 3879 lm Total Lamp Luminous Flux.(8log(F/F0) = 4.7)

C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2020-06-16

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
 Humidity:65.0%
 Test Distance:8.900m [K=1.0000]
 Remarks:

UTILIZATION FACTORS TABLE

Test:U:120.4V I:0.2267A P:27.22W PF:0.9973 Lamp Flux:3878.78x1 lm		
NAME: MLSN4-28/D10/U/35	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:1182*66*14mm	PROTECTION ANGLE:

REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	55	43	36	55	43	36	53	43	36	29
0.80	65	53	45	64	52	45	62	52	45	37
1.00	73	61	53	72	61	53	69	62	53	45
1.25	80	69	61	78	68	61	76	66	60	52
1.50	85	74	67	83	73	66	80	71	65	57
2.00	92	82	75	90	81	74	86	79	73	64
2.50	96	87	80	94	86	79	90	83	78	69
3.00	99	92	85	97	90	84	93	87	82	73
4.00	104	97	92	101	95	90	97	92	88	78
5.00	106	101	96	104	99	94	99	95	91	82
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2020-06-16

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
 Humidity:65.0%
 Test Distance:8.900m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:120.4V I:0.2267A P:27.22W PF:0.9973 Lamp Flux:3878.78x1 lm		
NAME: MLSN4-28/D10/U/35	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:1182*66*14mm	PROTECTION ANGLE:

Conical surface Flux(90deg):

1883 lm

%lum = 48.5%


%lamp = 48.5%

Conical surface Flux(120deg):

2783.3 lm

%lum = 71.8%

%lamp = 71.8%




C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2020-06-16

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
 Humidity:65.0%
 Test Distance:8.900m [K=1.0000]
 Remarks:

AAI Figure

Test:U:120.4V I:0.2267A P:27.22W PF:0.9973 Lamp Flux:3878.78x1 lm		
NAME: MLSN4-28/D10/U/35	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:1182*66*14mm	PROTECTION ANGLE:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2020-06-16

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
 Humidity:65.0%
 Test Distance:8.900m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM

Test:U:120.4V I:0.2267A P:27.22W PF:0.9973 Lamp Flux:3878.78x1 lm		
NAME: MLSN4-28/D10/U/35	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:1182*66*14mm	PROTECTION ANGLE:



C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: DAMIN
 Test Date: 2020-06-16

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.290
 Humidity: 65.0%
 Test Distance: 8.900m [K=1.0000]
 Remarks:

LED Avg.L Report

Test:U:120.4V I:0.2267A P:27.22W PF:0.9973 Lamp Flux:3878.78x1 lm		
NAME: MLSN4-28/D10/U/35	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:1182*66*14mm	PROTECTION ANGLE:


AvgL	cd/m2
L_0~180(65)av	2841
L_0~180(75)av	2342
L_0~180(85)av	1606
L_90~270(65)av	4819
L_90~270(75)av	6025
L_90~270(85)av	13147
L_45(65)av	3990
L_45(75)av	4616
L_45(85)av	9022

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2020-06-16

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
 Humidity:65.0%
 Test Distance:8.900m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2020-06-16

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity: 65.0%
Test Distance: 8.900m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:120.4V I:0.2267A P:27.22W PF:0.9973 Lamp Flux:3878.78x1 lm		
NAME: MLSN4-28/D10/U/35	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:1182*66*14mm	PROTECTION ANGLE:

Table--1

UNIT: cd

[illegible]

C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2020-06-16

```

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity:65.0%
Test Distance:8.900m [K=1.0000]
Remarks:

```

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:120.4V I:0.2267A P:27.22W PF:0.9973 Lamp Flux:3878.78x1 lm		
NAME: MLSN4-28/D10/U/35	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:1182*66*14mm	PROTECTION ANGLE:

Table--2

UNIT: cd

[illegible]

C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2020-06-16

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
 Humidity:65.0%
 Test Distance:8.900m [K=1.0000]
 Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:120.4V I:0.2267A P:27.22W PF:0.9973 Lamp Flux:3878.78x1 lm		
NAME: MLSN4-28/D10/U/35	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:1182*66*14mm	PROTECTION ANGLE:

Table--3

UNIT: cd

[illegible]

C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2020-06-16

```

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity:65.0%
Test Distance:8.900m [K=1.0000]
Remarks:

```

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:120.4V I:0.2267A P:27.22W PF:0.9973 Lamp Flux:3878.78x1 lm		
NAME: MLSN4-28/D10/U/35	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:1182*66*14mm	PROTECTION ANGLE:

Table--4

UNIT: cd

[illegible]

C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2020-06-16

```

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity:65.0%
Test Distance:8.900m [K=1.0000]
Remarks:

```