RODUCT HIGHLIGHTS



Key Features

- Up to 450W and 150 lm/W
- Multi Power, Multi CCT & Dual Voltage (120-347V)
- Shipped with V-Hooks, Chain & 10 FT. Cord
- Semi-Frosted PMMA lens
- Also available in R1, R2, R3 & R4 models

Quick Specs

Watts	Lumens	ССТ
340/380/420/450W	51,000/57,000/ 63,000/67,500lm	35/40/5000K



Key Features

- Up to 450W and 165 lm/W
- Multi Power, Multi CCT & Dual Voltage (120-347)
- Optional Plug-In Dimming Sensor
- IP66 Rated for outdoor locations
- Black finish, slimmer profile. Custom colours available*
- Also available in R1, R2, R3 & R4 models

Quick Specs

*Paint Charges apply

Watts	Lumens	ССТ
320/350/400/450W	52,800/57,750/ 66,000/74,250 lm	30/40/5000K



Key Features

- For 500mm x 1500mm (20" x 60") metric applications
- Up to 60W and 133 lm/W
- Multi Power, Multi CCT & Dual Voltage (120-347V)
- Recessed or suspended installation
- Backlit technology offers even lighting distribution

Quick Specs

Watts 30/40/50/60W		Lumens	ССТ	
		3,900/5,200/ 6,500/8,004 lm	35/40/5000K	



Key Features

- 40W output (15W and 25W models also available)
- Universal Input (100-347V)
- Designed for external mounting
- ≥90 minutes of emergency operating time
- Compatible with any ≤300W 0-10V dimmable LED fixtures

Quick Specs

Input Current	Input Power	Output Voltage	Output Power
100 mA	12W max	170VDC	40W

More info? renolighting.com

Questions? 905-604-4666





At RENO, we're committed to being Always On.™

Always On Innovation

Our very own R&D facility enables us to conceptualize and develop innovative lighting solutions that fit every project's needs.

Always On Service

Our dedication to speed, attention to detail, and indepth lighting knowledge is why customers love us.

Always On Your Side

Our relationship does not end after the sale. We promise to always be on your side, long after you've installed our products.